



Model Type: **EC-9225xxxx**  
 Dimension : **92 x 92 x 25 mm**

	Voltage	5V	12V	24V
			✓	
	Fan Speed	L	M	H
		1800	2200	2600
	Certificate	UL	CE	TUV
		✓	✓	✓
Bearing Type	Sleeve	1 Ball	2 Ball	EL
	✓	✓	✓	✓

Model Type: **EC-9225 II**  
 Dimension : **92 x 92 x 25 mm**

	Voltage	5V		12V		24V	
				✓		✓	
	Fan Speed	LL	L	M	H	HH	TH
		1200	1800	2200	2600	3000	3400
	Certificate	UL		CE		TUV	
		✓		✓		✓	
Bearing Type	Sleeve		1 Ball	2 Ball	EL		
	✓		✓	✓	✓		

Model	Voltage VDC	Current AMP	Input Watts	Fan Speed RPM	AirFlow CFM	Pressure InchH <sub>2</sub> O	Noise dBA	Life Hour
EC9225H12B	12	0.21	2.52	2600	48.43	0.11	<31	50000
EC9225H12C								35000
EC9225H12S								25000
EC9225H12E								40000
EC9225M12B	12	0.15	1.8	2200	39.35	0.08	<25	50000
EC9225M12C								35000
EC9225M12S								25000
EC9225M12E								40000
EC9225L12B	12	0.09	1.08	1800	31.84	0.05	<22	50000
EC9225L12C								35000
EC9225L12S								25000
EC9225L12E								40000
<b>EC-9225 II</b>								
EC9225HH12B	12	0.3	3.6	3000	61.11	0.14	<28.1	50000
EC9225HH12C								35000
EC9225HH12S								25000
EC9225HH12E								40000
EC9225H12B	12	0.24	2.88	2600	53.1	0.13	<25	50000
EC9225H12C								35000
EC9225H12S								25000
EC9225H12E								40000
EC9225M12B								50000

EC9225M12C	12	0.2	2.4	2200	42.1	0.09	<21.4	35000
EC9225M12S								25000
EC9225M12E								40000
EC9225L12B	12	0.16	1.92	1800	36.23	0.06	<17	50000
EC9225L12C								35000
EC9225L12S								25000
EC9225L12E								40000
EC9225LL12B	12	0.12	1.44	1200	24.15	0.03	<8.7	50000
EC9225LL12C								35000
EC9225LL12S								25000
EC9225LL12E								40000
EC9225TH24B	24	0.28	6.72	3400	67.47	0.18	<30.8	50000
EC9225TH24C								35000
EC9225TH24S								25000
EC9225TH24E								40000
EC9225HH24B	24	0.23	5.52	3000	61.11	0.14	<28.1	50000
EC9225HH24C								35000
EC9225HH24S								25000
EC9225HH24E								40000
EC9225H24B	24	0.18	4.32	2600	53.1	0.13	<25	50000
EC9225H24C								35000
EC9225H24S								25000
EC9225H24E								40000
EC9225M24B	24	0.13	3.12	2200	42.1	0.09	<21.4	50000
EC9225M24C								35000
EC9225M24S								25000
EC9225M24E								40000
EC9225L24B	24	0.08	1.92	1800	36.23	0.06	<17	50000
EC9225L24C								35000
EC9225L24S								25000
EC9225L24E								40000

**E--EL bearing, B -- Two ball bearing , C -- One ball One sleeve bearing, S -- Sleeve bearing**