

Ordering codes and packing units (lead spacing 22.5 mm)

V_R	V_{rms} $f \leq 1$ kHz	C_R	Max. dimensions w × h × l	Ordering code (composition see below)	Ammo pack	Reel	Untaped
VDC	VAC	nF	mm		pcs./unit	pcs./unit	pcs./unit
250	160	220	6.0 × 15.0 × 26.5	B32653A3224+***	680	700	720
		330	6.0 × 15.0 × 26.5	B32653A3334+***	680	700	720
		470	7.0 × 16.0 × 26.5	B32653A3474+***	580	600	630
		680	8.5 × 16.5 × 26.5	B32653A3684+***	480	500	510
		1000	10.5 × 16.5 × 26.5	B32653A3105+***	390	400	540
400	200	150	6.0 × 15.0 × 26.5	B32653A4154+***	680	700	720
		220	6.0 × 15.0 × 26.5	B32653A4224+***	680	700	720
		330	7.0 × 16.0 × 26.5	B32653A4334+***	580	600	630
		470	8.5 × 16.5 × 26.5	B32653A4474+***	480	500	510
		680	10.5 × 16.5 × 26.5	B32653A4684+***	390	400	540
		1000	11.0 × 20.5 × 26.5	B32653A4105+***	370	350	510
630	250	100	6.0 × 15.0 × 26.5	B32653A6104+***	680	700	720
		150	6.0 × 15.0 × 26.5	B32653A6154+***	680	700	720
		220	8.5 × 16.5 × 26.5	B32653A6224+***	480	500	510
		330	10.5 × 16.5 × 26.5	B32653A6334+***	390	400	540
		470	11.0 × 20.5 × 26.5	B32653A6474+***	370	350	510
1000	250	33	6.0 × 15.0 × 26.5	B32653A0333+***	680	700	720
		47	6.0 × 15.0 × 26.5	B32653A0473+***	680	700	720
		68	6.0 × 15.0 × 26.5	B32653A0683+***	680	700	720
		100	8.5 × 16.5 × 26.5	B32653A0104+***	480	500	510
		150	10.5 × 16.5 × 26.5	B32653A0154+***	390	400	540
		220	11.0 × 20.5 × 26.5	B32653A0224+***	370	350	510
1250	500	22	6.0 × 15.0 × 26.5	B32653A7223+***	680	700	720
		33	6.0 × 15.0 × 26.5	B32653A7333+***	680	700	720
		47	8.5 × 16.5 × 26.5	B32653A7473+***	480	500	510
		68	10.5 × 16.5 × 26.5	B32653A7683+***	390	400	540
		100	11.0 × 20.5 × 26.5	B32653A7104+***	370	350	510

Further E series and intermediate capacitance values on request.

Composition of ordering code

+ = Capacitance tolerance code:

K = ±10%

J = ±5%

on request = ±3.5%

*** = Packaging code:

289 = Ammo pack

189 = Reel

000 = Untaped (lead length 6 – 1 mm)


B32653
High pulse (wound)
Ordering codes and packing units (lead spacing 22.5 mm)

V_R	V_{rms} $f \leq 1$ kHz	C_R	Max. dimensions $w \times h \times l$ mm	Ordering code (composition see below)	Ammo pack pcs./unit	Reel pcs./unit	Untaped pcs./unit
VDC	VAC	nF					
1600	500	6.8	6.0 × 15.0 × 26.5	B32653A1682+***	680	700	720
		10	6.0 × 15.0 × 26.5	B32653A1103+***	680	700	720
		15	7.0 × 16.0 × 26.5	B32653A1153+***	580	600	630
		22	8.5 × 16.5 × 26.5	B32653A1223+***	480	500	510
		33	10.5 × 16.5 × 26.5	B32653A1333+***	390	400	540
		47	11.0 × 20.5 × 26.5	B32653A1473+***	370	350	510
2000	700	3.3	6.0 × 15.0 × 26.5	B32653A2332+***	680	700	720
		4.7	6.0 × 15.0 × 26.5	B32653A2472+***	680	700	720
		6.8	8.5 × 16.5 × 26.5	B32653A2682+***	480	500	510
		10	10.5 × 16.5 × 26.5	B32653A2103+***	390	400	540
		15	11.0 × 20.5 × 26.5	B32653A2153+***	370	350	510
2000	1000	2.2	6.0 × 15.0 × 26.5	B32653A8222+***	680	700	720
		3.3	6.0 × 15.0 × 26.5	B32653A8332+***	680	700	720
		4.7	8.5 × 16.5 × 26.5	B32653A8472+***	480	500	510
		6.8	10.5 × 16.5 × 26.5	B32653A8682+***	390	400	540
		10	10.5 × 20.5 × 26.5	B32653A8103+***	390	400	540

Further E series and intermediate capacitance values on request.

Composition of ordering code

+= Capacitance tolerance code:

K = ±10%

J = ±5%

on request = ±3.5%

*** = Packaging code:

289 = Ammo pack

189 = Reel

000 = Untaped (lead length 6 – 1 mm)