

FULL COLOR LED LAMPS

Model No. LEF-C5003D

Description:


- Super bright LED Lamp
- Full Color
- Round type
- T1-3/4 (5mm)diameter
- 4 pin
- With Flange
- Solder leads without stand-off
- Package : bulk

Features :

- High Luminous intensity
- Technology : AlGaInP / GaN / GaN
- Peak wavelength $\lambda_p = 630 / 528 / 472$ nm
- Common Cathode
- UV resistant epoxy

Selection guide :

Emitted Color	Material	Wavelength (nm)	Lens Color	Viewing Angle
Super Red	AlGaInP	630	White Diffused	45°
Super Green	GaN	528		
Super Blue	GaN	472		



Notes:

1. All dimensions are in millimeter.
2. Lead spacing is measured where the lead emerge from the package.

1. Green
2. Blue
3. Common Cathode
4. Red

FULL COLOR LED LAMPS

Model No. LEF-C5003D

Absolute Maximum Ratings ($T_a=25^{\circ}\text{C}$)

Parameter		Symbol	Max. Rating	Unit
Power Dissipation	Red	P_D	120	mW
	Green		120	
	Blue		120	
Peak Forward Current (1/10 Duty Cycle @1KHz)	Red	I_{PF}	200	mA
	Green		100	
	Blue		100	
Continuous Forward Current	Red	I_{AF}	50	mA
	Green		30	
	Blue		30	
Reverse Voltage		V_R	5.0	V
Operating Temperature Range	Red	T_{OPR}	-40~+85	$^{\circ}\text{C}$
	Green · Blue		-20~+80	
Storage Temperature Range	Red	T_{STG}	-40~+85	$^{\circ}\text{C}$
	Green · Blue		-30~+100	
Solder temperature 1.6mm from body for 3 seconds at 260°C				

Optical –Electrical Characteristics ($T_a=25^{\circ}\text{C}$)

Parameter		Symbol	Test condition	Min.	Typ.	Max.	Unit
Luminous Intensity	Red	IV	IF=20mA	420	600		mcd
	Green			700	1000		
	Blue			140	200		
Forward Voltage	Red	VF	IF=20mA		2.0	2.4	V
	Green				3.5	4.0	
	Blue				3.5	4.0	
Reverse Current	Red	IR	VR=5V			10	μA
	Green					10	
	Blue					10	
View Angle		$2\theta 1/2$	IF=20mA		45		deg.
Peak Wavelength	Red	λP	IF=20mA		630		nm
	Green				528		
	Blue				472		
Dominant Wavelength	Red	λD	IF=20mA		625		nm
	Green				525		
	Blue				470		
Spectrum Radiation Bandwidth	Red	$\Delta\lambda$	IF=20mA		20		nm
	Green				30		
	Blue				35		