

Round Type

φ 3.0 mm Series

Conventional Part No.	Global Part No.	Lighting Color
LN277RPX	LNG277RKR	Red
LN377GPX	LNG377GKG	Green
LN477YPX	LNG477YKX	Amber
LN877RPX	LNG877RKD	Orange

■ Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Lighting Color	P_D (mW)	I_F (mA)	I_{FP} (mA)*	V_R (V)	T_{opr} ($^\circ\text{C}$)	T_{stg} ($^\circ\text{C}$)
Red	70	25	150	4	-25 ~ +85	-30 ~ +100
Green	90	30	150	4	-25 ~ +85	-30 ~ +100
Amber	90	30	150	4	-25 ~ +85	-30 ~ +100
Orange	90	30	150	3	-25 ~ +85	-30 ~ +100

I_{FP} の条件は、 $duty$ 10%、Pulse width 1 msec. The condition of I_{FP} is duty 10%, Pulse width 1 msec

■ Electro-Optical Characteristics ($T_a = 25^\circ\text{C}$)

Conventional Part No.	Lighting Color	Lens Color	I_O			V_F		λ_P	$\Delta\lambda$	I_F	I_R	
			Typ	Min	I_F	Typ	Max	Typ	Typ		Max	V_R
LN277RPX	Red	Red Diffused	1.5	0.5	15	2.2	2.8	700	100	20	5	4
LN377GPX	Green	Green Diffused	5.0	2.0	20	2.2	2.8	565	30	20	10	4
LN477YPX	Amber	Amber Diffused	10.0	3.5	20	2.2	2.8	590	30	20	10	4
LN877RPX	Orange	Red Diffused	5.0	2.0	20	2.1	2.8	630	40	20	10	3
Unit	—	—	mcd	mcd	mA	V	V	nm	nm	mA	μA	V

