


Screw clamping terminal block- UKHV-10JD- 011363




Screw clamping terminal block, connection method : screw connection , number of connections : 3 , crimping range : 0.5mm² -16mm² , AWG : 20-6, thickness:10.2mm , height:46mm , color : yellow-green , mounting type : TH35-7.5、 TH35-15、 G32-15、 G32-18

Product parameter

| Parameter | Data |
|---------------------------------------|---------------|
| Packing unit (PCS) | 50 |
| NW per piece(g) | 30.7 |
| Layers | 1 |
| Number of connections | 3 |
| Rated cross section(mm ²) | 16 |
| Color | yellow-green |
| Insulation material | PA |
| Flame retardant grade (UL94) | V0 |
| Rated voltage(V) | / |
| Rated current(A) | / |
| Temperature of insulation material | -40 ~ +125 |
| Wire feed | Terminal side |

Product certification

| Parameter | Data |
|--------------------|--|
| Certification logo |  |

Technical data

| Parameter | Data |
|---|------------------|
| Connection Method | Screw connection |
| Screw thread | M4 |
| Stripping length(mm) | 10 |
| Tightening torque | 1.5-1.8 |
| Solid conductors(mm ²) | 0.5-16 |
| Solid conductors AWG | 20-6 |
| Stranded conductors(mm ²) | 0.5-10 |
| Stranded conductors AWG | 20-6 |
| Operating temperature () | -40 ~ +105 |
| Ambient temperature (storage/transportation) () | -25 ~ +60 |
| Relative humidity | 30% ~ 90% |
| Connection in acc. with standard | IEC 60947-7-1 |

Dimension

| Parameter | Data |
|---------------|------|
| Width(mm) | 42.5 |
| Thickness(mm) | 10.2 |
| Height(mm) | 46 |