


Screw clamping terminal block- UKHV-4 / 2 × 2JD- 011437




Screw clamping terminal block, connection method : screw connection , number of connections : 4 , crimping range : 0.2mm² -6mm² , AWG : 24-10, thickness:6.2mm , height:50.5mm , color : yellow-green , mounting type : TH35-7.5、 TH35-15、 G32-15、 G32-18

Product parameter

Parameter	Data
Packing unit (PCS)	80
NW per piece(g)	32.7
Layers	1
Number of connections	4
Rated cross section(mm ²)	6
Color	yellow-green
Insulation material	PA
Flame retardant grade (UL94)	V0
Rated voltage(V)	/
Rated current(A)	/
Temperature of insulation material	-40 ~ +125
Wire feed	Terminal side

Product certification

Parameter	Data
Certification logo	

Technical data

Parameter	Data
Connection Method	Screw connection
Screw thread	M3

Parameter	Data
Stripping length(mm)	8mm
Tightening torque	0.6-0.8Nm
Solid conductors(mm ²)	0.2-6
Solid conductors AWG	24-10
Stranded conductors(mm ²)	0.2-4
Stranded conductors AWG	24-10
Operating temperature ()	-40 ~ +105
Ambient temperature (storage/transportation) ()	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

Dimension

Parameter	Data
Width(mm)	63.6
Thickness(mm)	6.2
Height(mm)	50.5