

Spring-cage connection terminal block- UJ5-2.5W-421124






Terminal block, Rated voltage(A):800V, Rated current:24A, connection methods:spring-cage connection, number of connection:2, crimping range:0.08mm² -2.5mm², AWG : 28-14, thickness 6mm, height 28.5mm, color:grey, mounting rail:TH35-7.5、 TH35-15.

Product parameter

| Parameter | Data |
|---------------------------------------|--------------------|
| Packing unit(pcs) | 105 |
| NW per piece(g) | 5.5 |
| Layers | 1 |
| Number of connections | 2 |
| Rated cross section(mm ²) | 2.5 |
| Color | grey |
| Insulation material | PA |
| Flame retardant grade | V0 |
| Rated voltage(V) | 800 |
| Rated current(A) | 24 |
| Temperature of insulation material | -40 ~ +125 |
| Wire feed | Above the terminal |

Product certification

| Parameter | Data |
|--------------------|--|
| Certification logo |  |
| Certification logo |  |
| Certification logo | |

| Parameter | Data |
|--------------------|---|
| | IECE_x |
| Certification logo |  INMETRO |
| Certification logo | RoHS |

Technical data

| Parameter | Data |
|---|------------------------|
| Connection Method | Spring-cage connection |
| Stripping length(mm) | 9 |
| Solid conductors(mm ²) | 0.08-2.5 |
| Solid conductors AWG | 28-14 |
| Stranded conductors(mm ²) | 0.08-2.5 |
| Stranded conductors AWG | 28-14 |
| Operating temperature () | -40 ~ +105 |
| Ambient temperature (storage/transportation) () | -25 ~ +55 |
| Relative humidity | 30% ~ 90% |
| Connection in acc. with standard | IEC 60947-7-1 |

Dimension

| Parameter | Data |
|---------------|------|
| Width(mm) | 37.5 |
| Thickness(mm) | 6 |
| Height(mm) | 28.5 |