

Screw clamping terminal block- UKJ-35N-011087








Screw clamping terminal block , rated voltage:800V , Max. operating current:125A, connection method : screw connection , number of connections : 3 , crimping range : 0.75mm<sup>2</sup> -35mm<sup>2</sup> , thickness:15.2mm , height:49.8mm , color : grey , mounting type : TH35-7.5、 TH35-15、 G32-15、 G32-18

Product parameter

Parameter	Data
Packing unit (PCS)	40
NW per piece(g)	1.15
Layers	1
Number of connections	3
Rated cross section(mm <sup>2</sup> )	35
Color	grey
Insulation material	PA
Flame retardant grade ( UL94 )	V0
Rated voltage(V)	800
Rated current(A)	125
Temperature of insulation material	-40 ~ +125
Wire feed	Terminal side

Product certification

Parameter	Data
Certification logo	
Certification logo	

Parameter	Data
Certification logo	
Certification logo	
Certification logo	

## Technical data

Parameter	Data
Connection Method	Screw connection
Screw thread	M3
Stripping length(mm)	7
Tightening torque	0.6-0.8
Solid conductors(mm <sup>2</sup> )	0.75-35
Stranded conductors(mm <sup>2</sup> )	0.75-35
Operating temperature ( )	-40 ~ +105
Ambient temperature (storage/transportation) ( )	-25 ~ +60
Relative humidity	30% ~ 90%
Connection in acc. with standard	IEC 60947-7-1

## Dimension

Parameter	Data
Width(mm)	55
Thickness(mm)	15.2
Height(mm)	49.8